## NSN 5930-00-726-3444

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-726-3444

Body Style:
Hole mounted
Overall Length:
0.780 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Overall Height:
1.930 inches
Overall Width:
0.370 inches
Body Length:
0.780 inches
Body Width:
0.370 inches
Body Height:
0.359 inches
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Style:
Round
Actuator Diameter:
0.092 inches
Actuator Free Position Height:
0.330 inches
Actuator Adapter Style:
Pushbutton
Adapter Bushing Length:
0.410 inches
Maximum Voltage Rating In Volts:
250.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal
Thready Qty Per Inch (tpi):
40
Thread Size:
0.250 inches
Nonpile-up Contact Arrangement:

Nonplic up Contact Arrangement.

1 pole, double throw, one position momentary single switch unit

## **NSN 5930-00-726-3444** Sensitive Switch - Page 2 of 2



Switch Release Force:
1.0 ounces
Switch Actuating Force:
5.0 ounces
Actuator Movement:
Between 0.004 pretravel inches and 0.005 overtravel inches and 0.004 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac
Thread Series Designator:
Uns
Terminal Type And Quantity:
3 solder stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A053a0