NSN 5930-00-726-4108

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-726-4108
Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Driptight
Overall Length:
3.060 inches
Overall Height:
1.530 inches
Overall Width:
1.530 inches
Actuator Length:
1.500 inches
Actuator Style:
Adjustable arm
Actuator Diameter:
0.190 inches
Actuator Height:
1.240 inches
Actuator Width:
2.500 inches
Housing Diameter:
1.530 inches
Housing Length:
1.820 inches
Housing Bushing Length:
0.340 inches
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Features Provided:
Actuator seal
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
2 two circuit, double break/double make, one position momentary single switch unit
Actuator Movement:

20.0 differential degrees

NSN 5930-00-726-4108

Sensitive Switch - Page 2 of 2



Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

-	~ · · · ·	—	
Inroad	SALIDE	LIDEIAN	Otor.
Thread	oci ico	Desidi	ialui.

Uns

Terminal Type And Quantity:

8 wire lead

Specification Data:

81349-mil-s-8805/49 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0