

View Online at <https://aerobasegroup.com/nsn/5930-00-727-0007>

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

8.094 inches

**Overall Height:**

4.750 inches

**Overall Width:**

4.750 inches

**First Flat Length:**

1.125 inches single actuator

**Flat Height:**

0.281 inches single actuator

**Shaft Diameter:**

0.375 inches single actuator

**Shaft Length:**

1.500 inches single actuator

**Unthreaded Mounting Hole Diameter:**

0.406 inches 1st mounting facility and 0.410 inches 1st mounting facility

**Individual Section Quantity:**

4

**Knob Manufacturer Code:**

82121

**Knob Manufacturer Part Number:**

A

**Longest Horizontal Distance Between Mounting Centers:**

3.781 inches 1st mounting facility

**Longest Vertical Distance Between Mounting Centers:**

3.781 inches 1st mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section rear

**Throw Quantity:**

3 each section rear

**Mounting Method:**

Bracket 2nd mounting facility

**Features Provided:**

Actuator knob

**Contact Voltage Rating In Volts:**

500.0 ac at sea level

**Mounting Facility Pattern:**

Four position rectangular 1st mounting facility

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Round, flatted, threaded hole single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

60.0 amperes resistive load ac at sea level

**Style Designator:**

Tap, circuit selector

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0