## NSN 5930-00-727-3006



Sensitive Switch - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5930-00-727-3006 **Body Style:** Hole mounted **Center To Center Distance Between Mounting Facilities Parallel To Length:** 0.520 inches **Body Length:** 1.250 inches **Body Width:** 0.594 inches **Case Material: Plastic Center To Center Distance Between Mounting Facilities Parallel To Height:** 0.312 inches **Actuator Style:** Round **Maximum Voltage Rating In Volts:** 250.0 ac and 30.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Unthreaded hole **Nonpile-up Contact Arrangement:** 1 two circuit, double break/double make, one position momentary single switch unit **Switch Release Force:** 4.0 ounces **Switch Actuating Force:** 12.0 ounces **Actuator Movement:** Between 0.060 pretravel inches and 0.015 overtravel inches and 0.020 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 10.000 amperes resistive dc and 10.000 amperes resistive ac **Precious Material And Location:** Contact surfaces gold and contacts silver **Terminal Type And Quantity:** 4 tab, solder lug Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A053a0