

View Online at <https://aerobasegroup.com/nsn/5930-00-727-8088>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Explosion proof and watertight

**Overall Length:**

2.500 inches

**Overall Height:**

4.125 inches

**Overall Width:**

1.218 inches

**Actuator Length:**

1.296 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

Between 1.094 inches and 1.156 inches

**Actuator Roller Diameter:**

0.500 inches

**Actuator Roller Width:**

0.125 inches

**Housing Height:**

1.250 inches

**Housing Length:**

2.500 inches

**Housing Width:**

1.218 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Height:**

1.563 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

1.875 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

2 two circuit, double break/double make, one position momentary single switch unit

**Switch Actuating Force:**

64.0 ounces

**Actuator Movement:**

Between 0.100 pretravel inches and 0.281 overtravel inches and 0.062 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive dc and 10.000 amperes inductive dc and 5.000 amperes lamp dc and 10.000 amperes resistive ac and 10.000 amperes inductive ac and 6.000 amperes lamp ac

**Terminal Type And Quantity:**

1 connector, receptacle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0