NSN 5930-00-728-0281

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-728-0281

Overall Length:
1.312 inches
Outside Diameter:
0.125 inches single connection
Overall Height:
1.094 inches
Overall Width:
1.125 inches
Body Length:
1.137 inches
Pressure Switch Type:
Absolute
Operating Tempurature Rating:
Between -55.0 degrees celsius and 125.0 degrees celsius
Mounting Method:
Line
Thready Qty Per Inch (tpi):
27 single pressure connection
Contact Action Stimulus:
Decrease
Proof Pressure:
24.00 pounds per square inch absolute
Thread Size:
0.125 inches single pressure connection
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Turret
Contact Load Current Rating:
4.0 amperes resistive load second voltage and 2.5 amperes inductive load second voltage and 2.0 amperes lamp load second voltage
Contact Adjustability:
Actuation point not adjustable and deactuation point not adjustable
Contact Stimulus Rating:
17.00 actuation point pounds per square inch absolute and 15.20 deactuation point pounds per square inch absolute
Contact Voltage Rating In Volts:
28.0 dc at sea level second voltage
Pressure Connector Type:

Frequency In Hertz:

400.0 first voltage

Media For Which Designed:

Flared, threaded external single connection

Gas

NSN 5930-00-728-0281

Pressure Switch - Page 2 of 2



Style Designator:
Cylindrical
Thread Series Designator:
Anpt single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0