

View Online at <https://aerobasegroup.com/nsn/5930-00-728-0562>

Body Style:

Hole mounted

Overall Length:

0.789 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.360 inches and 0.390 inches

Overall Height:

0.680 inches

Overall Width:

0.250 inches

Body Length:

Between 0.779 inches and 0.789 inches

Body Width:

Between 0.240 inches and 0.260 inches

Body Height:

0.510 inches

Unthreaded Mounting Hole Diameter:

Between 0.087 inches and 0.090 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Strategic weapon systems; radar (highpar) an/gpn-22 (v); aircraft, stratolifter c-135; aircraft, (ac-130h, mc-130h. Ec-130e, hc-130); helicopter,

Inclosure Type:

Hermetically sealed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

7.0 ounces

Actuator Movement:

Between 0.030 pretravel inches and 0.003 overtravel inches and 0.006 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes lamp dc and 4.000 amperes resistive ac and 2.000 amperes inductive ac and 500.000 milliamperes lamp ac

Special Features:

Weapon system essential

Test Data Document:

81349-mils8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0