

View Online at <https://aerobasegroup.com/nsn/5930-00-728-4328>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Weatherproof

Bushing Length:

Between 0.458 inches and 0.478 inches

Body Length:

1.336 inches

Body Width:

0.734 inches

Unthreaded Mounting Hole Diameter:

0.087 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.237 inches and 0.243 inches

Actuator Height:

Between 0.655 inches and 0.719 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Missile minuteman lgm-30

Mounting Surface To Terminal End Distance:

1.250 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

25.000 amperes resistive dc and 15.000 amperes inductive dc and 7.000 amperes motor dc and 25.000 amperes resistive ac and 15.000 amperes inductive ac and 7.000 amperes motor ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0