

View Online at <https://aerobasegroup.com/nsn/5930-00-728-4544>

Thread Class:

2b 1st mounting facility

Thread Length:

0.500 inches 2nd mounting facility

Overall Length:

12.908 inches

Overall Height:

2.812 inches

Overall Width:

2.812 inches

Shaft Length:

0.375 inches single actuator

Individual Section Quantity:

27

Longest Horizontal Distance Between Mounting Centers:

2.297 inches 1st mounting facility

Longest Vertical Distance Between Mounting Centers:

2.297 inches 1st mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Facility Circle Radius:

0.906 inches 2nd mounting facility

Mounting Method:

Threaded hole 1st mounting facility

Thready Qty Per Inch (tpi):

24 1st mounting facility

Thread Size:

0.190 inches 2nd mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Mounting Facility Pattern:

Four position circular 1st mounting facility

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Rectangular/square, threaded hole single actuator

Criticality Code Justification:

Feat

Square Shaft Size:

0.250 inches single actuator

Terminal Type:

Tab w/screw

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Detent Rotational Torque Range:

+34.000/+41.000 inch-pounds single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Special Features:

Decks 3-8 mbb, decks 9-27 bbm

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unf 2nd mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0