

View Online at <https://aerobasegroup.com/nsn/5930-00-728-4545>

**Thread Class:**

2b 1st mounting facility

**Thread Length:**

0.500 inches 2nd mounting facility

**Overall Length:**

12.908 inches

**Overall Height:**

2.812 inches

**Overall Width:**

2.812 inches

**Shaft Length:**

0.375 inches single actuator

**Individual Section Quantity:**

27

**Longest Horizontal Distance Between Mounting Centers:**

2.297 inches 1st mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.297 inches 1st mounting facility

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Facility Circle Radius:**

0.906 inches 2nd mounting facility

**Mounting Method:**

Threaded hole 1st mounting facility

**Thready Qty Per Inch (tpi):**

24 1st mounting facility

**Thread Size:**

0.190 inches 2nd mounting facility

**Contact Voltage Rating In Volts:**

125.0 ac at sea level

**Mounting Facility Pattern:**

Four position circular 1st mounting facility

**Switch Actuator Indexing Position Quantity:**

8 single actuator

**Shaft Type:**

Rectangular/square, threaded hole single actuator

**Criticality Code Justification:**

Feat

**Square Shaft Size:**

0.250 inches single actuator

**Terminal Type:**

Tab w/screw

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Detent Rotational Torque Range:**

+34.000/+41.000 inch-pounds single actuator

**Switch Actuator Stop Device Type:**

Adjustable stop single actuator

**Contact Load Current Rating:**

10.0 amperes resistive load ac at sea level

**Special Features:**

Deck 3 mbb, decks 4 -27 bbm

**Precious Material And Location:**

Contact surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Unf 2nd mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0