# NSN 5930-00-728-5576

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-728-5576

### **Thread Class:**

2a single mounting facility

#### Thread Length:

0.375 inches single mounting facility

### **Overall Length:**

1.562 inches

#### **Overall Height:**

1.189 inches

#### **Overall Width:**

1.125 inches

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.375 inches single actuator

#### Individual Section Quantity:

1

# Nonturn Device Type:

Slotted bushing at 12: 00 o'clock

## Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

1 single section front

#### Throw Quantity:

7 single section rear

#### **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

30.0 dc at sea level

#### Switch Actuator Indexing Position Quantity:

7 single actuator

#### Shaft Type:

Round single actuator

#### **Terminal Type:**

Tab, solder lug

#### **Contact Switching Action:**

Breaks before makes single section rear

# Switch Actuator Positioning Increment:

30.0 degrees single actuator

#### **Detent Rotational Torque Range:**

+0.500/+2.000 inch-pounds single actuator

# NSN 5930-00-728-5576

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 500.0 milliamperes resistive load dc at sea level Style Designator: Square wafer, panel mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A052b0