

View Online at <https://aerobasegroup.com/nsn/5930-00-728-7822>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Bushing Length:

0.470 inches

Body Length:

0.840 inches

Body Width:

1.312 inches

Body Height:

0.978 inches

Actuator Style:

Round

Actuator Diameter:

0.428 inches

Actuator Height:

1.180 inches

Actuator Position-action Relationship:

Left position maintained and right position maintained

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

End Application:

Moored training ship, los angeles class ssn (688), sturgeon class ssn (637), underwater torpedo tubes, submarine armament and fire control systems, submarine ship control and navigation systems, submarine interior communication system, armament system, submarine communications and antenna systems

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 3.000 amperes resistive ac

Special Features:

Weapon system essential

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0