

View Online at <https://aerobasegroup.com/nsn/5930-00-728-9908>

**Body Style:**

Bushing/hole mounted

**Overall Length:**

0.701 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.500 inches

**Overall Height:**

2.000 inches

**Overall Width:**

1.250 inches

**Bushing Length:**

0.359 inches

**Body Length:**

0.701 inches

**Body Width:**

1.250 inches

**Body Height:**

0.813 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.140 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.500 inches

**Actuator Height:**

0.516 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

4 two circuit, double break/double make, one position momentary single switch unit

**Switch Release Force:**

8.0 ounces

**Switch Actuating Force:**

64.0 ounces

**Actuator Movement:**

Between 0.250 pretravel inches and 0.012 overtravel inches and 0.025 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

16 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0