

View Online at <https://aerobasegroup.com/nsn/5930-00-728-9908>

Body Style:

Bushing/hole mounted

Overall Length:

0.701 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches

Overall Height:

2.000 inches

Overall Width:

1.250 inches

Bushing Length:

0.359 inches

Body Length:

0.701 inches

Body Width:

1.250 inches

Body Height:

0.813 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.140 inches

Actuator Style:

Round

Actuator Diameter:

0.500 inches

Actuator Height:

0.516 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

4 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

8.0 ounces

Switch Actuating Force:

64.0 ounces

Actuator Movement:

Between 0.250 pretravel inches and 0.012 overtravel inches and 0.025 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

Thread Series Designator:

Unef

Terminal Type And Quantity:

16 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0