

View Online at <https://aerobasegroup.com/nsn/5930-00-729-0526>

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Overall Length:

4.532 inches

First Flat Length:

0.438 inches single actuator

Flat Height:

0.185 inches single actuator and 0.189 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.844 inches single actuator

Nonturn Device Radius:

0.531 inches at 10: 30 o'clock

Individual Section Quantity:

8

Nonturn Device Type:

Tab at 10: 30 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

23 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Shaft Flat/slot Angular Location:

157.5 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

24 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

15.0 degrees single actuator

Contact Load Current Rating:

1.5 amperes resistive load ac at sea level

Precious Material And Location:

Clips and rotor blades silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0