NSN 5930-00-729-1662

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-729-1662

Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.391 inches
Body Length:
0.886 inches
Body Width:
0.356 inches
Body Height:
0.600 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
Between 0.087 inches and 0.090 inches
Actuator Style:
Round
Actuator Diameter:
0.078 inches
Actuator Height:
0.115 inches
Actuator Free Position Height:
Between 0.405 inches and 0.445 inches
Maximum Voltage Rating In Volts:
250.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
Between 5.0 ounces and 17.0 ounces
Actuator Movement:
Between 0.050 pretravel inches and 0.003 overtravel inches and 0.004 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
3.000 amperes inductive dc and 5.000 amperes resistive ac
Terminal Type And Quantity:
2 wire lead
Shelf Life:
N/a

NSN 5930-00-729-1662

Sensitive Switch - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A053a0