## NSN 5930-00-729-1663

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-729-1663

| Thread Class:   |
|---|
| 2a single pressure connection   |
| Overall Length:   |
| 3.437 inches  |
| Outside Diameter:   |
| 0.500 inches single connection  |
| Overall Width:  |
| 3.625 inches  |
| Body Diameter:  |
| 3.000 inches  |
| Body Length:  |
| 2.312 inches  |
| Unthreaded Mounting Hole Diameter:  |
| 0.406 inches  |
| Distance Between Mounting Facility Centers:   |
| 3.000 inches  |
| Pressure Switch Type:   |
| Gage  |
| Operating Tempurature Rating:   |
| 700.0 degrees fahrenheit  |
| Mounting Method:  |
| Unthreaded hole   |
| Thready Qty Per Inch (tpi):   |
| 14 single pressure connection   |
| Contact Action Stimulus:  |
| Increase  |
| Thread Size:  |
| 0.500 inches single pressure connection   |
| Mounting Facility Pattern:  |
| Two position in-line  |
| Nonpile-up Contact Arrangement:   |
| 1 pole, single throw, both positions maintained   |
| Terminal Type:  |
| Wire lead   |
| Contact Load Current Rating:  |
| 5.0 amperes resistive load single voltage   |
| Contact Adjustability:  |
| Deactuation point adjustable and actuation point adjustable   |
| Contact Adjustment Range:   |
| +1.00/+100.00 actuation point pounds per square inch and -4.00/+5.00 deactuation point pounds per square inch |

**Contact Adjustment Type:** 

External deactuation point screw and external actuation point screw

## NSN 5930-00-729-1663

Pressure Switch - Page 2 of 2



## Contact Voltage Rating In Volts: 28.0 dc at sea level single voltage Pressure Connector Type: Plain, threaded external single connection Media For Which Designed: Gas Style Designator: Cylindrical w/mounting lugs Thread Series Designator: Npt single pressure connection Shelf Life: N/a Unit Of Measure: --

**Demilitarization:** 

No Fiig: A048b0