NSN 5930-00-729-2692

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-729-2692 **Thread Class:** 2a single mounting facility **Overall Length:** 4.750 inches **Overall Height:** 2.750 inches **Overall Width:** 2.750 inches First Flat Length: 0.562 inches single actuator Flat Height: 0.188 inches single actuator **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.938 inches single actuator **Individual Section Quantity:** 2 **Longest Horizontal Distance Between Mounting Centers:** 1.500 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical **Mounting Method:** Threaded bushing single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.164 inches single mounting facility **Contact Voltage Rating In Volts:** 115.0 ac at sea level **Mounting Facility Pattern:** Two position in-line single mounting facility **Switch Actuator Indexing Position Quantity:** 4 single actuator **Shaft Type:** Round, flatted single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes each section front **Switch Actuator Positioning Increment:**

22.5 degrees single actuator

NSN 5930-00-729-2692

Rotary Switch - Page 2 of 2



Contact Load Current Ratin

2.0 amperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0