NSN 5930-00-729-3663

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-729-3663

view Online at https://aerobasegroup.com/nsn/59
Thread Class:
2a single mounting facility
Thread Length:
0.380 inches single mounting facility
Overall Length:
2.000 inches
Overall Height:
1.000 inches
Overall Width:
0.940 inches
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
0.870 inches single actuator
Nonturn Device Radius:
0.375 inches at 3: 00 o'clock
Individual Section Quantity:
1
Nonturn Device Type:
Tab at 3: 00 o'clock
Operating Tempurature Range:
-65.0/+100.0 degrees celsius
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 single section rear
Throw Quantity:
2 single section rear
Mounting Method:
Threaded bushing single mounting facility
Thread Size:
0.375 inches single mounting facility
Contact Voltage Rating In Volts:
28.0 dc at sea level
Switch Actuator Indexing Position Quantity:
2 single actuator
Shaft Type:
Round single actuator
Terminal Type:
Tab, solder lug
Contact Switching Action:

Breaks before makes single section rear

NSN 5930-00-729-3663

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment: 60.0 degrees single actuator **Switch Actuator Stop Device Type:** Fixed stop single actuator **Contact Load Current Rating:** 1.0 amperes resistive load ac at sea level **Precious Material And Location:** Contacts and rotors silver **Precious Material:** Silver Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No Fiig: A052b0