NSN 5930-00-729-7109

Rotary Switch - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5930-00-729-7109
Overall Length:
2.218 inches
Overall Height:
2.125 inches
Overall Width:
2.000 inches
Shaft Diameter:
0.375 inches single actuator
Shaft Length:
0.750 inches single actuator
Unthreaded Mounting Hole Diameter:
0.188 inches single mounting facility
Individual Section Quantity:
2
Longest Horizontal Distance Between Mounting Centers:
1.438 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
1.750 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 each section front
Throw Quantity:
2 each section front
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Contact Voltage Rating In Volts:
30.0 lowest dc voltage rating at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
1 single actuator
Shaft Type:
Round, slotted single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:

Fixed stop single actuator

NSN 5930-00-729-7109

Rotary Switch - Page 2 of 2



Contact Load Current Rating:

5.0 amperes resistive load lowest dc voltage rating at sea level and 2.5 amperes inductive load lowest dc voltage rating at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0