NSN 5930-00-729-7789

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-729-7789

view Crimie at https://aerobasegroup.com/nsi//os
Thread Class:
2a single mounting facility
Thread Length:
0.375 inches single mounting facility
Overall Length:
3.625 inches
Overall Height:
1.500 inches
Overall Width:
0.875 inches
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
2.250 inches single actuator
Overall Diameter:
1.312 inches
Individual Section Quantity:
2
Knob Manufacturer Code:
71590
Knob Manufacturer Part Number:
Knob Manufacturer Part Number.
P120
P120
P120 Switch Contact Basic Design:
P120 Switch Contact Basic Design: Nonpile-up symmetrical
P120 Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity:
P120 Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 3 each section rear
P120 Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 3 each section rear Throw Quantity:
P120 Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 3 each section rear Throw Quantity: 3 each section rear
P120 Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 3 each section rear Throw Quantity: 3 each section rear Mounting Method:
P120 Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 3 each section rear Throw Quantity: 3 each section rear Mounting Method: Threaded bushing single mounting facility
Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 3 each section rear Throw Quantity: 3 each section rear Mounting Method: Threaded bushing single mounting facility Features Provided:
P120 Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 3 each section rear Throw Quantity: 3 each section rear Mounting Method: Threaded bushing single mounting facility Features Provided: Actuator knob
Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 3 each section rear Throw Quantity: 3 each section rear Mounting Method: Threaded bushing single mounting facility Features Provided: Actuator knob Thread Size:
Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 3 each section rear Throw Quantity: 3 each section rear Mounting Method: Threaded bushing single mounting facility Features Provided: Actuator knob Thread Size: 0.375 inches single mounting facility
Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 3 each section rear Throw Quantity: 3 each section rear Mounting Method: Threaded bushing single mounting facility Features Provided: Actuator knob Thread Size: 0.375 inches single mounting facility Contact Voltage Rating In Volts:
Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 3 each section rear Throw Quantity: 3 each section rear Mounting Method: Threaded bushing single mounting facility Features Provided: Actuator knob Thread Size: 0.375 inches single mounting facility Contact Voltage Rating In Volts: 15.0 dc at sea level
Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 3 each section rear Throw Quantity: 3 each section rear Mounting Method: Threaded bushing single mounting facility Features Provided: Actuator knob Thread Size: 0.375 inches single mounting facility Contact Voltage Rating In Volts: 15.0 dc at sea level Switch Actuator Indexing Position Quantity:
Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 3 each section rear Throw Quantity: 3 each section rear Mounting Method: Threaded bushing single mounting facility Features Provided: Actuator knob Thread Size: 0.375 inches single mounting facility Contact Voltage Rating In Volts: 15.0 dc at sea level Switch Actuator Indexing Position Quantity: 4 single actuator

Tab, solder lug

NSN 5930-00-729-7789

Rotary Switch - Page 2 of 2



Contact	Switching	Action:
CUIILACL	SWILCIIIII	ACLIOII.

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

2.0 amperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0