NSN 5930-00-729-8161

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-729-8161

Hazardous Locations/environmental Protection:
Moisture proof
Overall Length:
4.375 inches
Overall Height:
2.812 inches
Overall Width:
2.812 inches
Shaft Diameter:
0.374 inches single actuator
Shaft Length:
0.812 inches single actuator
Unthreaded Mounting Hole Diameter:
0.213 inches single mounting facility
Individual Section Quantity:
5
Knob Manufacturer Code:
10001
Knob Manufacturer Part Number:
1323803
Longest Horizontal Distance Between Mounting Centers:
2.298 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.298 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 each section rear
Throw Quantity:
1 each section rear
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
125.0 dc at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
1 single actuator
Shaft Type:

Round, slotted single actuator

NSN 5930-00-729-8161

Rotary Switch - Page 2 of 2



Terminal Type:
Tab w/screw
Contact Switching Action:
Makes before breaks 3rd section rear
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
5.0 amperes resistive load dc at sea level
Style Designator:
Tap, circuit selector
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A052b0