## NSN 5930-00-729-8465

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-729-8465

Body Style:
Hole mounted
Overall Length:
4.000 inches
Overall Height:
3.625 inches
Overall Width:
1.297 inches
Case Material:
Plastic
Actuator Style:
Roller plunger
Actuator Free Position Height:
1.484 inches
Actuator Roller Diameter:
0.656 inches
Actuator Roller Width:
0.187 inches
Housing Height:
2.156 inches
Housing Width:
1.156 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Height:
1.625 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
3.250 inches
Maximum Voltage Rating In Volts:
460.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
12.0 ounces
Switch Actuating Force:
40.0 ounces
Actuator Movement:
Between 0.094 pretravel inches and 0.156 overtravel inches and 0.010 differential inches

Contact Load Current Rating At Maximum Rated Voltage: 250.000 milliamperes resistive dc and 20.000 amperes resistive ac

## NSN 5930-00-729-8465

Sensitive Switch - Page 2 of 2



Special	Features:
---------	-----------

Right hand actuator

**Terminal Type And Quantity:** 

3 screw

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

Yes - demil/mli

Fiig:

A053a0