## NSN 5930-00-730-0432

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-730-0432

## Thread Length:

0.312 inches single mounting facility

## Hazardous Locations/environmental Protection:

Watertight

## **Overall Length:**

1.052 inches

#### First Flat Length:

0.250 inches single actuator

#### Flat Height:

0.219 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.562 inches single actuator

#### **Overall Diameter:**

1.015 inches

#### Nonturn Device Radius:

0.375 inches at 3: 00 o'clock

## Individual Section Quantity:

1

Nonturn Device Type:

Slotted bushing at 3: 00 o'clock

#### Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

1 single section front

#### **Throw Quantity:**

9 single section rear

#### Mounting Method:

Threaded bushing single mounting facility

#### Thread Size:

0.375 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

115.0 dc at sea level

#### Shaft Flat/slot Angular Location:

135.0 degrees from nonturn device single actuator

#### **Rotor Through Connection Quantity:**

1 single section

### Switch Actuator Indexing Position Quantity:

9 single actuator

Shaft Type:

Round, flatted single actuator

# NSN 5930-00-730-0432

Rotary Switch - Page 2 of 2



**Terminal Type:** 

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Style Designator:

Snap or line

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0