NSN 5930-00-730-1284

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-730-1284 **Body Style:** Hole mounted **Overall Length:** 0.781 inches **Center To Center Distance Between Mounting Facilities Parallel To Length:** 0.375 inches **Overall Height:** 0.747 inches **Overall Width:** 0.250 inches **Body Length:** 0.781 inches **Body Width:** 0.250 inches **Body Height:** 0.356 inches **Unthreaded Mounting Hole Diameter:** 0.088 inches **Actuator Length:** 0.251 inches **Actuator Style:** Roller arm **Actuator Free Position Height:** Between 0.500 inches and 0.620 inches **Actuator Roller Diameter:** 0.187 inches **Actuator Roller Width:** 0.125 inches **Actuator Adapter Style:** Roller arm **Maximum Voltage Rating In Volts:** 250.0 ac and 30.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Unthreaded hole **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit **Switch Release Force:** 7.0 grams **Switch Actuating Force:**

40.0 grams

NSN 5930-00-730-1284

Sensitive Switch - Page 2 of 2



Actuator Movement:

Between 0.085 pretravel inches and 0.011 overtravel inches and 0.019 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0