

View Online at <https://aerobasegroup.com/nsn/5930-00-730-1285>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.375 inches

**Body Width:**

2.120 inches

**Case Material:**

Plastic

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

1.500 inches

**Switch Actuator Quantity:**

1

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

3.030 inches

**Actuator Roller Diameter:**

0.875 inches

**Actuator Roller Width:**

0.300 inches

**Housing Height:**

1.920 inches

**Housing Length:**

6.620 inches

**Housing Width:**

2.420 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

3.375 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

1.500 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

0.312 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

20.0 ounces

**Contact Load Current Rating At Maximum Rated Voltage:**

750.000 milliamperes resistive dc and 30.000 amperes resistive ac

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0