

View Online at <https://aerobasegroup.com/nsn/5930-00-730-1285>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.375 inches

Body Width:

2.120 inches

Case Material:

Plastic

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.500 inches

Switch Actuator Quantity:

1

Actuator Style:

Roller arm

Actuator Free Position Height:

3.030 inches

Actuator Roller Diameter:

0.875 inches

Actuator Roller Width:

0.300 inches

Housing Height:

1.920 inches

Housing Length:

6.620 inches

Housing Width:

2.420 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

3.375 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.500 inches

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Thready Qty Per Inch (tpi):

18

Thread Size:

0.312 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

20.0 ounces

Contact Load Current Rating At Maximum Rated Voltage:

750.000 milliamperes resistive dc and 30.000 amperes resistive ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0