# NSN 5930-00-730-3876

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-730-3876

## **Thread Class:**

2a single mounting facility

## Thread Length:

0.375 inches single mounting facility

# **Overall Height:**

1.500 inches

## **Overall Width:**

1.313 inches

#### Shaft Diameter:

0.265 inches 1st actuator

#### Shaft Length:

1.126 inches 2nd actuator

#### **Nonturn Device Radius:**

0.438 inches at 9:00 o'clock

### Individual Section Quantity:

2

#### Nonturn Device Type:

Tab at 9: 00 o'clock

## **Operating Tempurature Range:**

-62.0/+85.0 degrees celsius

# Switch Contact Basic Design:

Nonpile-up symmetrical

### Pole Quantity:

1 each section rear

### **Throw Quantity:**

11 each section rear

### **Mounting Method:**

Threaded bushing single mounting facility

### **Thread Size:**

0.375 inches single mounting facility

### Contact Voltage Rating In Volts:

28.0 dc at sea level

### Switch Actuator Indexing Position Quantity:

11 2nd actuator

### Shaft Type:

Round, hollowed 1st actuator

### **Terminal Type:**

Tab, solder lug

### **Contact Switching Action:**

Makes before breaks each section rear

### Switch Actuator Positioning Increment:

30.0 degrees 2nd actuator

# NSN 5930-00-730-3876

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type: Fixed stop all actuators **Contact Load Current Rating:** 500.0 milliamperes resistive load ac at sea level Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A052b0