

View Online at <https://aerobasegroup.com/nsn/5930-00-730-6623>

Thread Class:

2a

Body Style:

Bushing mounted

Overall Length:

2.966 inches

Overall Height:

1.000 inches

Overall Width:

1.000 inches

Body Diameter:

Between 0.970 inches and 1.030 inches

Bushing Length:

Between 0.595 inches and 0.655 inches

Body Length:

1.075 inches

Actuator Style:

Roller plunger

Actuator Free Position Height:

1.781 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

64.0 ounces

Switch Actuating Force:

192.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 4.000 amperes motor dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

Thread Series Designator:

Unef

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0