## NSN 5930-00-731-7495

Lever Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-731-7495

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Fungus resistant and corrosion resistant
Overall Length:
5.094 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.812 inches
Overall Height:
1.657 inches
Overall Width:
1.500 inches
Body Length:
3.500 inches
Body Width:
1.500 inches
Body Height:
1.657 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.125 inches
Actuator Style:
Round
Actuator Height:
1.594 inches
Actuator Position-action Relationship:
Up position maintained and down position maintained and center position maintained
Actuator Position-locking Relationship:
Up position no locking action and down position no locking action and center position locked in
Maximum Voltage Rating In Volts:
120.0 ac
Inclosure Type:
Uninclosed
Mounting Method:
Unthreaded hole
Thready Qty Per Inch (tpi):
40
Pile-up Contact Form Arrangement:
4a single position
Thread Size:
0.112 inches
Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive ac

## NSN 5930-00-731-7495

Lever Switch - Page 2 of 2



<b>Precious Material And Location:</b>
Contacts silver
Thread Series Designator:
Unf
Terminal Type And Quantity:
8 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A053a0