## NSN 5930-00-731-7502

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-731-7502 **Overall Height:** 2.125 inches **Body Diameter:** 5.750 inches **Distance Between Mounting Facility Centers:** 2.000 inches **Capillary Tube Length:** 10.0 inches **Bulb Length:** 3.000 inches **Bulb Diameter:** 0.688 inches **Tempurature Sensing Element Type:** Bulb **Operating Tempurature Rating:** 220.0 degrees fahrenheit **Mounting Method:** Bracket and unthreaded hole **Features Provided:** Tubing end seal connection **Contact Action Stimulus:** Increase **Mounting Facility Pattern:** Two position in-line **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally closed, momentary action **Terminal Type:** Screw **Contact Load Current Rating:** 5.0 amperes resistive load first voltage **Contact Adjustability:** Deactuation point adjustable and actuation point adjustable **Contact Adjustment Range:** +100.00/+200.00 actuation point degrees fahrenheit and +100.00/+200.00 deactuation point degrees fahrenheit **Contact Adjustment Type:** External deactuation point screw and external actuation point knob **Contact Voltage Rating In Volts:** 

230.0 ac at sea level first voltage

Media For Which Designed:

Gas or liquid

**Style Designator:** 

Disc

## NSN 5930-00-731-7502

Thermostatic Switch - Page 2 of 2



_					
C.	~~	14	I i	ife:	
J.	16			HE.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0