## NSN 5930-00-732-1942

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-732-1942

## Thread Class:

2a single mounting facility

## Thread Length:

0.250 inches single mounting facility

## **Overall Length:**

1.313 inches

## Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.438 inches single actuator

## **Overall Diameter:**

1.000 inches

## **Nonturn Device Radius:**

0.375 inches at 1: 30 o'clock

## Individual Section Quantity:

1

## Nonturn Device Type:

Tab at 1: 30 o'clock

## **Operating Tempurature Range:**

-25.0/+85.0 degrees celsius

## Switch Contact Basic Design:

Nonpile-up nonsymmetrical

## Mounting Method:

Threaded bushing single mounting facility

## **Thread Size:**

0.375 inches single mounting facility

## **Contact Voltage Rating In Volts:**

28.0 dc at sea level

## Switch Actuator Indexing Position Quantity:

7 single actuator

## Shaft Type:

Round single actuator

## **Terminal Type:**

Tab, solder lug

## Contact Switching Action:

Makes before breaks single section rear

## Switch Actuator Positioning Increment:

30.0 degrees single actuator

## **Detent Rotational Torque Range:**

+10.000/+60.000 inch-ounces single actuator

## Switch Actuator Stop Device Type:

Fixed stop single actuator

# NSN 5930-00-732-1942

Rotary Switch - Page 2 of 2



**Contact Load Current Rating:** 

1.0 amperes resistive load ac at sea level

## Precious Material And Location:

Terminal surfaces silver

**Precious Material:** 

Silver

## Style Designator:

Circular wafer, bushing mount

## **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A052b0