NSN 5930-00-732-2350

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-732-2350

view Online at https://aerobasegroup.com/hsh/3330-00-732-2330
Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Vaportight
Overall Length:
1.685 inches
Overall Height:
0.790 inches
Overall Width:
0.656 inches
Bushing Length:
0.310 inches
Body Width:
0.656 inches
Body Height:
0.790 inches
Actuator Diameter:
0.323 inches
Actuator Height:
0.190 inches
Actuator Color:
Black single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Hermetically sealed
Mounting Method:
Unthreaded bushing
Features Provided:
Actuator seal
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
2 pole, double throw, two positions momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac
Thread Series Designator:
Uns
Terminal Type And Quantity:

6 tab, solder lug

NSN 5930-00-732-2350

Push Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0