## NSN 5930-00-732-5200

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-732-5200

| Overall Length:   |
|---|
| 7.750 inches  |
| Overall Height:   |
| 2.125 inches  |
| Body Diameter:  |
| 5.750 inches  |
| Unthreaded Mounting Hole Diameter:  |
| 0.219 inches  |
| Distance Between Mounting Facility Centers:   |
| 2.000 inches  |
| Capillary Tube Length:  |
| 240.0 inches  |
| Bulb Length:  |
| 3.000 inches  |
| Bulb Diameter:  |
| 0.688 inches  |
| Tempurature Sensing Element Type:   |
| Capillary tube-bulb   |
| Operating Tempurature Rating:   |
| 220.0 degrees fahrenheit  |
| Mounting Method:  |
| Bracket and unthreaded hole   |
| Features Provided:  |
| Hermetically sealed case and tubing end seal connection   |
| Contact Action Stimulus:  |
| Increase  |
| Mounting Facility Pattern:  |
| Two position in-line  |
| Nonpile-up Contact Arrangement:   |
| 1 pole, single throw, normally open, momentary action   |
| Terminal Type:  |
| Screw   |
| Contact Load Current Rating:  |
| 5.0 amperes resistive load second voltage   |
| Contact Adjustability:  |
| Actuation point adjustable and deactuation point adjustable   |
| Contact Adjustment Range:   |
| +100.00/+200.00 actuation point degrees fahrenheit and +100.00/+200.00 deactuation point degrees fahrenheit |
| Contact Adjustment Type:  |
| External actuation point knob and external deactuation point knob   |
| Contact Voltage Rating In Volts:  |
| 230.0 dc at sea level fourth voltage  |

## NSN 5930-00-732-5200

Thermostatic Switch - Page 2 of 2



| Media For Which Designed: |
|---------------------------|
| Gas or liquid             |
| Style Designator:         |
| Cylindrical w/port        |
| Shelf Life:               |
| N/a                       |
| Unit Of Measure:          |
|                           |
| Demilitarization:         |
| No                        |

**Fiig:** A048b0