## NSN 5930-00-732-5584

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-732-5584

**Thread Class:** 2b single mounting facility **Overall Length:** 10.313 inches **Overall Height:** 2.750 inches **Overall Width:** 2.750 inches First Flat Length: 0.687 inches single actuator Flat Height: 0.216 inches single actuator **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 5.938 inches single actuator **Individual Section Quantity:** 3 **Longest Horizontal Distance Between Mounting Centers:** 1.500 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 2 each section rear **Throw Quantity:** 6 each section rear **Mounting Method:** Threaded hole single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.164 inches single mounting facility **Contact Voltage Rating In Volts:** 115.0 ac at sea level **Mounting Facility Pattern:** Two position in-line single mounting facility **Switch Actuator Indexing Position Quantity:** 6 single actuator **Shaft Type:** Round, flatted single actuator **Terminal Type:** 

Tab, solder lug

## NSN 5930-00-732-5584

Rotary Switch - Page 2 of 2



Con	tact	Swit	chino	ı Acti	on:
	ıavı	OWIL	CHILL	ı Actı	vii.

Breaks before makes each section rear

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

**Contact Load Current Rating:** 

2.0 amperes resistive load ac at sea level

Style Designator:

Tap, square frame

**Thread Series Designator:** 

Unc single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0