NSN 5930-00-733-2754

Rotary Switch - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5930-00-733-2754

2a single mounting facility Thread Length: 0.500 inches single mounting facility **Overall Length:** 4.875 inches **Overall Height:** 1.875 inches **Overall Width:** 1.625 inches First Flat Length: 0.375 inches single actuator Flat Height: 0.219 inches single actuator **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.500 inches single actuator **Nonturn Device Radius:** 0.375 inches at 9: 00 o'clock **Individual Section Quantity:** 5 **Nonturn Device Type:** Tab at 9: 00 o'clock **Switch Contact Basic Design:** Nonpile-up nonsymmetrical **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 6 single actuator **Shaft Type:** Round, flatted single actuator **Terminal Type:** Tab, solder lug **Switch Actuator Positioning Increment:** 30.0 degrees single actuator

Switch Actuator Stan Davisa Tu

Switch Actuator Stop Device Type:

Fixed stop single actuator

NSN 5930-00-733-2754

Rotary Switch - Page 2 of 2



Contact Load	Current	Rating:
--------------	---------	---------

1.0 amperes resistive load dc at sea level

Precious Material And Location:

Contacts and rotors silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0