

View Online at <https://aerobasegroup.com/nsn/5930-00-733-2939>

Hazardous Locations/environmental Protection:

Vibration proof

Overall Length:

10.250 inches

Overall Height:

3.750 inches

Overall Width:

2.250 inches

First Flat Length:

0.560 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.440 inches single actuator

Unthreaded Mounting Hole Diameter:

0.115 inches single mounting facility

Individual Section Quantity:

7

Longest Horizontal Distance Between Mounting Centers:

3.375 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.875 inches single mounting facility

Operating Temperature Range:

-0.0/+185.0 degrees fahrenheit

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

4 each section periphery

Throw Quantity:

5 each section periphery

Mounting Method:

Base single mounting facility and unthreaded hole single mounting facility

Contact Voltage Rating In Volts:

118.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, v flatted single actuator

Terminal Type:

Turret

Contact Switching Action:

Breaks before makes each section periphery

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

2.0 amperes resistive load ac at sea level

Style Designator:

Tap, square frame

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0