

View Online at <https://aerobasegroup.com/nsn/5930-00-733-2945>

Thread Class:

2b single mounting facility

Overall Length:

4.660 inches

Overall Height:

2.250 inches

Overall Width:

2.570 inches

First Flat Length:

0.560 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

2.750 inches single actuator

Unthreaded Mounting Hole Diameter:

0.164 inches single mounting facility

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.500 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

4 single section periphery

Throw Quantity:

3 single section periphery

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.164 inches single mounting facility

Contact Voltage Rating In Volts:

118.0 ac at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, v flatted single actuator

Terminal Type:

Turret

Contact Switching Action:

Breaks before makes single section periphery

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

2.0 amperes resistive load ac at sea level

Special Features:

Crosstalk shall not exceed 40db down with 2000 ohms between terminals and ground and a 2v rms 2 kc signal applied to any terminal

Style Designator:

Tap, square frame

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0