

View Online at <https://aerobasegroup.com/nsn/5930-00-733-2946>

Hazardous Locations/environmental Protection:

Vibration proof

Overall Length:

6.190 inches

Overall Height:

4.000 inches

Overall Width:

3.310 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.940 inches single actuator

Unthreaded Mounting Hole Diameter:

0.203 inches single mounting facility

Individual Section Quantity:

4

Longest Horizontal Distance Between Mounting Centers:

3.625 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.375 inches single mounting facility

Operating Temperature Range:

+0.0/+185.0 degrees fahrenheit

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

6 each section periphery

Throw Quantity:

8 each section periphery

Mounting Method:

Base single mounting facility and unthreaded hole single mounting facility

Contact Voltage Rating In Volts:

118.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Turret

Contact Switching Action:

Breaks before makes each section periphery

Switch Actuator Positioning Increment:

15.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

2.0 amperes resistive load ac at sea level

Style Designator:

Tap, square frame

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0