

View Online at <https://aerobasegroup.com/nsn/5930-00-735-1678>

Thread Class:

2a single mounting facility

Thread Length:

0.256 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.636 inches

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

0.656 inches single actuator

Overall Diameter:

0.512 inches

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 9: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section rear

Throw Quantity:

5 single section rear

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Metallic inclosure

Thready Qty Per Inch (tpi):

40 single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed-adjustable stops single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load ac at sea level

Style Designator:

Miniature, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0