

View Online at <https://aerobasegroup.com/nsn/5930-00-735-5450>

**Thread Class:**

2a single threaded hole

**Overall Length:**

Between 2.500 inches and 2.625 inches

**Overall Height:**

1.250 inches

**Overall Width:**

Between 1.469 inches and 1.594 inches

**Body Length:**

Between 1.984 inches and 2.016 inches

**Mounting Method:**

Threaded hole

**Thready Qty Per Inch (tpi):**

32 single threaded hole

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.190 inches single threaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

5.0 amperes resistive load first voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

785.00 actuation point feet per minute and 809.00 actuation point feet per minute and 825.00 actuation point feet per minute and 700.00 deactuation point feet per minute and 567.00 deactuation point feet per minute and 522.00 deactuation point feet per minute

**Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

**Media For Which Designed:**

Gas

**Style Designator:**

Rectangular

**Thread Series Designator:**

Unc single threaded hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0