

View Online at <https://aerobasegroup.com/nsn/5930-00-735-6973>

Thread Class:

2a single pressure connection

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

4.500 inches

Outside Diameter:

0.438 inches single connection

Overall Height:

1.875 inches

Overall Width:

2.594 inches

Body Length:

3.500 inches

Pressure Switch Type:

Gage

Mounting Method:

Input port

Contact Action Stimulus:

Increase

Proof Pressure:

500.00 pounds per square inch

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

5.0 amperes resistive load first voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+0.00/+250.00 actuation point pounds per square inch

Contact Adjustment Type:

External actuation point screw

Contact Voltage Rating In Volts:

600.0 ac at sea level second voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Rectangular

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0