NSN 5930-00-736-8733

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-736-8733

Overall Length:
2.380 inches
Overall Height:
3.062 inches
Overall Width:
2.850 inches
First Flat Length:
0.560 inches single actuator
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
1.470 inches single actuator
Unthreaded Mounting Hole Diameter:
0.185 inches single mounting facility
Individual Section Quantity:
1
Longest Horizontal Distance Between Mounting Centers:
2.125 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.722 inches single mounting facility
Operating Tempurature Range:
+0.0/+185.0 degrees fahrenheit
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
3 single section periphery
Throw Quantity:
2 single section periphery
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Contact Voltage Rating In Volts:
118.0 ac at sea level
Mounting Facility Pattern:
Two position diagonal single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Shaft Type:
Round, v flatted single actuator
Terminal Type:
Turret
Contact Switching Action:

Breaks before makes each section periphery

NSN 5930-00-736-8733Rotary Switch - Page 2 of 2

Fiig: A052b0



Switch Actuator Positioning Increment:
60.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
2.0 amperes resistive load ac at sea level
Special Features:
Crosstalk shall not exceed 40db down w/2000 ohms between terminals and ground and a 2v rms 2 kc signal applied to any terminal
Style Designator:
Tap, square frame
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No