

View Online at <https://aerobasegroup.com/nsn/5930-00-736-8733>

**Overall Length:**

2.380 inches

**Overall Height:**

3.062 inches

**Overall Width:**

2.850 inches

**First Flat Length:**

0.560 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

1.470 inches single actuator

**Unthreaded Mounting Hole Diameter:**

0.185 inches single mounting facility

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

2.125 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.722 inches single mounting facility

**Operating Temperature Range:**

+0.0/+185.0 degrees fahrenheit

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

3 single section periphery

**Throw Quantity:**

2 single section periphery

**Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

**Contact Voltage Rating In Volts:**

118.0 ac at sea level

**Mounting Facility Pattern:**

Two position diagonal single mounting facility

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round, v flatted single actuator

**Terminal Type:**

Turret

**Contact Switching Action:**

Breaks before makes each section periphery

**Switch Actuator Positioning Increment:**

60.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

2.0 amperes resistive load ac at sea level

**Special Features:**

Crosstalk shall not exceed 40db down w/2000 ohms between terminals and ground and a 2v rms 2 kc signal applied to any terminal

**Style Designator:**

Tap, square frame

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0