Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-736-8733

Overall	Length:
Overail	Longui.

- 2.380 inches
- **Overall Height:**

3.062 inches

Overall Width:

2.850 inches

First Flat Length:

0.560 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.470 inches single actuator

Unthreaded Mounting Hole Diameter:

0.185 inches single mounting facility

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

2.125 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.722 inches single mounting facility

Operating Tempurature Range:

+0.0/+185.0 degrees fahrenheit

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

3 single section periphery

Throw Quantity:

2 single section periphery

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Contact Voltage Rating In Volts:

118.0 ac at sea level

Mounting Facility Pattern:

Two position diagonal single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, v flatted single actuator

Terminal Type:

Turret

Contact Switching Action:

Breaks before makes each section periphery

NSN 5930-00-736-8733

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

60.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

2.0 amperes resistive load ac at sea level

Special Features:

Crosstalk shall not exceed 40db down w/2000 ohms between terminals and ground and a 2v rms 2 kc signal applied to any terminal

Style Designator:

Tap, square frame

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0