

View Online at <https://aerobasegroup.com/nsn/5930-00-737-8356>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

1.562 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.375 inches single actuator

Overall Diameter:

0.750 inches

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 12: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

4 single section front

Throw Quantity:

2 single section front

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Metallic inclosure

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Shaft Flat/slot Angular Location:

255.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0