

View Online at <https://aerobasegroup.com/nsn/5930-00-738-1313>

**Thread Class:**

2b single mounting facility

**Hazardous Locations/environmental Protection:**

Dustproof and explosion proof

**Overall Length:**

4.485 inches

**First Flat Length:**

0.500 inches single actuator

**Flat Height:**

0.210 inches single actuator

**Shaft Diameter:**

0.247 inches single actuator

**Shaft Length:**

0.905 inches single actuator

**Overall Diameter:**

1.970 inches

**Individual Section Quantity:**

5

**Longest Horizontal Distance Between Mounting Centers:**

1.594 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section rear

**Throw Quantity:**

8 each section front

**Mounting Method:**

Threaded hole single mounting facility

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.138 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Rotor Through Connection Quantity:**

1 each section

**Mounting Facility Pattern:**

Two position in-line single mounting facility

**Switch Actuator Indexing Position Quantity:**

8 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Screw

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Adjustable stop single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load dc at sea level

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0