NSN 5930-00-738-1640

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-738-1640

Thread Class: 2b single pressure connection **Thread Length:** 0.531 inches single pressure connection **Overall Length:** 3.200 inches **Overall Height:** 2.000 inches **Overall Width:** 2.000 inches **Distance Between Mounting Facility Centers:** 3.000 inches **Pressure Switch Type:** Gage **Operating Tempurature Rating:** Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit **Mounting Method:** Base Thready Qty Per Inch (tpi): 20 single pressure connection **Contact Action Stimulus:** Increase **Proof Pressure:** 200.00 pounds per square inch **Thread Size:** 0.750 inches single pressure connection **Mounting Facility Pattern:** Two position in-line **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally closed, momentary action **Sensing Element Burst Pressure:** 400.00 pounds per square inch gage **Terminal Type:** Connector, receptacle **Contact Load Current Rating:** 3.0 amperes resistive load single voltage **Contact Adjustability:** Deactuation point not adjustable and actuation point not adjustable **Contact Stimulus Rating:** 27.00 actuation point pounds per square inch gage and 25.00 deactuation point pounds per square inch gage and 2.00 differential point

Contact Voltage Rating In Volts:

pounds per square inch gage

29.0 dc at sea level single voltage

NSN 5930-00-738-1640

Pressure Switch - Page 2 of 2



Pressure Connector Type:
Plain, threaded internal single connection
Media For Which Designed:
Liquid
Style Designator:
Rectangular
Thread Series Designator:
Nptf single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0