NSN 5930-00-738-4083

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-738-4083

Body Style	e:
Hole moun	ted
Center To	Center Distance Between Mounting Facilities Parallel To Length:
0.375 inch	es
Body Leng	gth:
0.781 inch	es
Body Wid	th:
0.250 inch	es
Body Heig	jht:
0.356 inch	es
Unthreade	ed Mounting Hole Diameter:
0.098 inch	es
Actuator S	Style:
Round	
Actuator I	Diameter:
0.023 inch	es
Actuator F	Free Position Height:
0.088 inch	es
Maximum	Voltage Rating In Volts:
30.0 dc	
Inclosure	Туре:
Fully enclo	sed
Mounting	Method:
Unthreade	d hole
Nonpile-u	p Contact Arrangement:
1 pole, do	uble throw, both positions maintained single switch unit
Switch Re	lease Force:
1.0 ounces	5
Switch Ac	tuating Force:
5.0 ounces	5
Actuator M	Novement:
Between 0	.020 pretravel inches and 0.003 overtravel inches and 0.004 differential inches
Contact L	oad Current Rating At Maximum Rated Voltage:
1.000 amp	eres resistive dc
Precious I	Material And Location:
Contact go	ld
Terminal 7	Type And Quantity:
3 solder st	ud
Shelf Life:	
N/a	
Unit Of Me	220110-

NSN 5930-00-738-4083

Sensitive Switch - Page 2 of 2

Demilitarization:

No

Fiig:

A053a0

