NSN 5930-00-738-9106

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-738-9106

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Weatherproof
Actuator Style:
Round
Actuator Diameter:
0.328 inches
Actuator Height:
0.078 inches
Actuator Free Position Height:
1.318 inches
Housing Height:
2.000 inches
Housing Length:
2.625 inches
Housing Width:
1.438 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
3.500 inches
Maximum Voltage Rating In Volts:
120.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal
Thread Size:
0.190 inches
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
Switch Release Force: 10.0 ounces
10.0 ounces
10.0 ounces Switch Actuating Force:
10.0 ounces Switch Actuating Force: 54.0 ounces
10.0 ounces Switch Actuating Force: 54.0 ounces Actuator Movement:
10.0 ounces Switch Actuating Force: 54.0 ounces Actuator Movement: Between 0.078 pretravel inches and 0.187 overtravel inches and 0.005 differential inches
10.0 ounces Switch Actuating Force: 54.0 ounces Actuator Movement: Between 0.078 pretravel inches and 0.187 overtravel inches and 0.005 differential inches Contact Load Current Rating At Maximum Rated Voltage:

NSN 5930-00-738-9106

Sensitive Switch - Page 2 of 2



Terminal Type Ar	nd Quantity:
------------------	--------------

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0